

## LEGEND:

- (1) (3) DOUBLE STRAND GALV. 12 GA. WIRE GUYS SPACED EQUALLY AROUND TREE COVER WITH 3/8" DIA x3" WHITE PVC TUBING
- (2) REFER TO STANDARD MVLI-563-0 FOR IRRIGATION METHOD
- (3) USE TRUNK GUARD WHERE TREE IS INSTALLED IN TURF AREAS
- (4) 4" BERM TO FORM DEPRESSED WATERING BASIN
- (5) 3" THICK SHREDDED MULCH IN PLANTER
- (6) PLANT TABS PER MANUFACTURER'S RECOMMENDATIONS
- (7) ROOT BALL
- (8) NEW RUBBER HOSE OVER WIRE AT POINT OF CONNECTION
- (9) BACKFILL MIX PER SPECIFICATIONS
- (10) REDWOOD DEADMAN PER DETAIL THIS SHEET, ALTERNATE METHOD PER CITY EQUIPMENT LIST
- (11) TURF
- (12) PLANTING PIT TO BE 2 TIMES THE WIDTH OF ROOT BALL & SAME DEPTH AS THE ROOT BALL

## NOTES:

- 1) INSTALL GUYS HAND TAUT TO PREVENT DEFORMATION OF LIMBS.
- 2) PLACE FERTILIZER TABS IN BOX PRIOR TO PLANTING FOR OBSERVATION.
- 3) ALTERNATE DEADMAN ASSEMBLY.

NOT TO SCALE





## CITY OF MORENO VALLEY

FINANCIAL & MANAGEMENT SERVICES DEPARTMENT - SPECIAL DISTRICTS DIVISION

STANDARD PLAN

TREE GUYING DETAIL 36" BOX OR LARGER

MVLI-510A-0 SHEET 1 OF 2