

- ELECTRICAL METER/IRRIGATION CONTROLLER ENCLOSURE PER SPECIFICATIONS
 - (2) 5/8" x 8' COPPER-CLAD GROUNDING ROD (GROUND 110 & CONTROLLER)
- DUPLEX OUTLET (CONDUIT PATH TO SERVICE PANEL PER CODE). INSTALL W/ SURGE ARRESTOR - ISOBAR ULTRABLOCK 428
- (4) APPLIANCE GRADE 110 VAC 3-WIRE CONDUCTOR POWER CORD (SIZED TO REACH DUPLEX OUTLET). SECURE TO CONTROLLER CABINET
- 4" SCH 40 E.C. SWEEP ELL FOR UF CONTROL WIRE ONLY
 - (6) 3/4" SCH 40 E.C. SWEEP ELL W/ NYLON PULL ROPE FOR FUTURE MOISTURE SENSOR WIRING
- TERMINAL STRIP FOR CONNECTION OF UF FIELD WIRE FROM SWEEP.
- (8) TERMINAL STRIP TO CONTROLLER (TYP.)
- #6 SOLID COPPER WIRE FROM GROUNDING ROD TO CONTROLLER GROUND LUG
 - (10) BRASS / BRONZE GROUND CLAMP
- TELEMETRY CONDUIT 3/4". EXTEND RAIN / WEATHER SENSOR CABLE INTO ENCL 36" MIN. FROM END OF SWEEP $\widehat{(12)}$ 12" THICK CONCRETE FOOTING POURED ON COMPACTED SUBGRADE (95% COMPACTION). RADIUS EDGES @ 1/2"
- ELECTRIC METER
- (14) IRRIGATION CONTROLLER MODEL # PER PLAN CALL-OUT
- RAIN GAUGE / WEATHER SENSOR MODEL # PER PLAN CALL-OUT
 - (16) FLOW SENSING COMPONENTS (INSTALL IF SHOWN ON PLAN) MODEL #'S PER PLAN CALL-OUT
- 2½" SCH 40 ELECTRICAL CONDUIT
 - (18)1" SCH 40 ELECTRICAL CONDUIT
- (19) STAINLESS STEEL VANDAL PROOF MESH COVER PER SPECIFICATIONS

NOTES:

- 1) COMMON WIRE TO BE WHITE, PER SPECIFICATIONS. PILOT WIRES TO BE SIZED AND COLOR PER SPECIFICATIONS.
- 2) NO SPLICES ALLOWED BETWEEN TERMINAL STRIP AND RCV.
- INSTALL EXTRA WIRES PER SPECIFICATION TO FARTHEST RCV IN ANY / ALL DIRECTIONS FROM ENCLOSURE. LOOP INTO EACH VALVE BOX ALONG WIRE PATH.
- IF FLOW SENSOR AND/OR MASTER VALVE IS INSTALLED, INCLUDE ¾" CONDUIT PATH FROM ENCLOSURE TO VAULTS.
- 5) SEE CITY STANDARD EQUIPMENT LIST FOR MANUFACTURER.

NOT TO SCALE



RECOMMENDED DIVISION MANAGER DATE APPROVED PUBLIC WORKS DIRECTOR / CITY ENGINEER

0F

FINANCIAL & MANAGEMENT SERVICES DEPARTMENT - SPECIAL DISTRICTS DIVISION

SMART CONTROLLER

ENCLOSURE DETAIL

STANDARD PLAN

MVLI-531B-0

SHEET 2 OF 2